

DTIC FILE COPY


2

Final Report  
on  
Contract No. N00014-89-C-0081

Investigation of OBS Bottom-Coupling Characteristics and Excess Noise  
Submitted to the  
Office of Naval Research

AD-A222 971

DTIC  
ELECTE  
JUN 20 1990  
S D



Rondout Associates, Incorporated  
P.O. Box 224  
Stone Ridge, NY 12484  
(914) 687-9150

June 1, 1990

DISTRIBUTION STATEMENT A  
Approved for public release  
Distribution Unlimited

90 06 18 209

The scientific objectives of this research were to perform coupling/noise OBS field tests designed to provide quantitative estimates of the coupling distortion and excess noise to be expected from high quality newly designed OBS's; to provide data required for transfer functions to compensate for the coupling distortion; and to suggest further improvements in instrumentation design and deployment procedures. The specific objectives of this contract were to organize and conduct field test and analyses of the bottom coupling characteristics and excess noise of new and renovated ocean-bottom seismographs. This research was in support of the instrument development being conducted under the ONR Accelerated Research Initiative (ARI) on ULF/VLF Ocean Seismo-acoustics. It was conducted in close cooperation with A. Tréhu of Oregon State University.

Signal distortion and excess noise from bottom currents, especially on the horizontal components, have continually plagued OBS users. There is disagreement within the community on how serious the problems are and on the best way to improve the situation. The OBS intercomparison tests conducted at Lopez Island in 1978, over ten years ago (Sutton *et al.*, 1981), and a few subsequent studies have suggested improved design concepts. Shallow burial and proper packaging and density distribution should greatly improve coupling, especially for horizontal components. It should also reduce noise induced by bottom currents (Sutton and Duennebier, 1987). Possible noise and signal distortion produced by a separated recording package also is not well understood at this time.

Because of delays in development of the new ONR OBS, tests originally scheduled for spring were conducted in November. Those and subsequent series of experiments are designed to measure: (1) the coupling characteristics of the new ONR OBS; (2) the seismic energy radiated from the main package of the ONR OBS as a function of frequency and distance from the seismometer package; (3) the effect of near-bottom currents on OBS-seafloor coupling of the new sensor package and on the radiation of energy from the main package; and (4) the effects of shallow burial on signal distortion and noise. The results from these tests should permit us to compare the coupling response of the new ONR and other OBS in order to correct for differences between instruments in subsequent seafloor experiments using arrays comprised of different types of OBS. The results will also enable us to estimate how far the sensor package should be deployed from the main recording package for the ONR OBS.

Research conducted under this contract included planning, preparation for, and conduct of the November field tests. A related paper was prepared and published (Sutton and Duennebier, 1989).



Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input checked="" type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	<div style="border: 1px solid black; padding: 2px; display: inline-block;">A-1</div>

## REFERENCES

- Sutton, G. H., F. K. Duennebier, B. Iwatake, J. D. Tuthill, B. T. R. Lewis, and J. Ewing, "An overview and general results of the Lopez Island OBS experiment," *Marine Geophysical Researches*, vol. 5, pp. 3-34, 1981.
- Sutton, G. H. and F. K. Duennebier, "Optimum design of ocean bottom seismometers," *Marine Geophysical Researches*, vol. 9, pp. 47-65, D. Reidel Publishing Company, 1987.
- Sutton, G. H. and F. K. Duennebier, "Avoiding signal distortion and excess noise in OBS," *Proceedings of a Workshop on Exploration of Deep Continental Margin Crust with Closely Spaced Shots and Receivers*, pp. A21-A22 (with 4 pp. of figures), Houston Area Research Center, M. Talwani, P. L. Stotta, and W. D. Mooney, ed., 1989.

## REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT  Unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S)			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION  Rondout Associates, Incorporated		6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION  Office of Naval Research		
6c. ADDRESS (City, State and ZIP Code) P.O. Box 224 Stone Ridge, NY 12484			7b. ADDRESS (City, State and ZIP Code) 800 N. Quincy St. Arlington, VA 22217-5000		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER  Contract No. N00014-89-C-0081		
8c. ADDRESS (City, State and ZIP Code)			10. SOURCE OF FUNDING NOS.		
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
				425p005--001	WORK UNIT NO.
11. TITLE (Include Security Classification) Investigation of OBS Bottom-Coupling Characteristics and Excess Noise					
12. PERSONAL AUTHOR(S)					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM 15 Feb 89 to 30 Nov 90		14. DATE OF REPORT (Yr., Mo., Day) 01 June 1990	
				15. PAGE COUNT 3	
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB. GR.	Ocean-bottom Seismographs (OBS), OBS-bottom Coupling, OBS-excess noise, OBS operational field tests		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>The scientific objectives of this research were to perform coupling/noise OBS field tests designed to provide quantitative estimates of the coupling distortion and excess noise to be expected from high quality newly designed OBS's; to provide data required for transfer functions to compensate for the coupling distortion; and to suggest further improvements in instrumentation design and deployment procedures. The specific objectives of this contract were to organize and conduct field test and analyses of the bottom coupling characteristics and excess noise of new and renovated ocean-bottom seismographs. This research was in support of the instrument development being conducted under the ONR Accelerated Research Initiative (ARI) on ULF/VLF Ocean Seismo-acoustics. Because of delays in development of the new ONR OBS, tests originally scheduled for spring were conducted in November. Research conducted under this contract included planning, preparation for, and conduct of the November field tests.</p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT  UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS <input type="checkbox"/>			21. ABSTRACT SECURITY CLASSIFICATION		
22a. NAME OF RESPONSIBLE INDIVIDUAL			22b. TELEPHONE NUMBER (Include Area Code)		22c. OFFICE SYMBOL